NORMALUX

ARQUE

Technical datasheet

Emergency Lighting

Ref. QSEIDL-150Li

LED

UNE 60598-2-22
230V 50/60HZ

Emergency Lighting: ARQUE. Reference: QSEIDL-150Li, manufactured by Normalux. Lumens 130 lm. Autonomy (h) 1h. Operating mode: Mantained - Non Maintained. Installation: Surface Mounting. Light source: Led. Battery of: LiFePO4 3.2V/600mAh. IP: 65. IK: 09. Version: DALI. Color: White. Casing: Polycarbonate. Voltage: 230V 50/60Hz. Dimensions (mm): 97 x 97 x 67 mm. Manufactured according UNE 60598-2-22 regulations.

Lumens	130 lm
Color temperatures (K)	5700
Light source	Led
Autonomy (h)	1h
Battery	LiFePO4 3.2V/600mAh
Power (W)	2,5W
Operating mode	Mantained - Non Maintained
Class	II
IP	65
IK	09
Operating temperature (ºC)	5 to 35
Remote control	Yes

Dimensions (mm):



Photometric data:



Parque tecnológico de Asturias. Calle Ablanal 1, 33428 Llanera (Asturias), Spain
T. +34 985 267 100 F. +34 985 266 992
normagrup@normagrup.com
www.normalux.com

Normagrup
Sense of Technology