

# URO

Emergency Lighting  
Ref. UAL3-500



**UNE 60598-2-22**  
**230V 50/60HZ**

Emergency Lighting: URO. Reference: UAL3-500, manufactured by Normalux. Lumens 500 lm. Autonomy (h) 3h. Operating mode: Maintained - Non Maintained. Installation: Surface Mounting. Light source: Led. Battery of: 2 x Ni-MH 3,6V/2700mAh. IP: 65. IK: 10. Version: Self-test. Color: White. Casing: Polycarbonate. Voltage: 230V 50/60Hz. Dimensions (mm): 350 x 350 x 80 mm. Manufactured according UNE 60598-2-22 regulations. Compatible with S-TE remote control.

Models with presence detector (UL-300P, UL-700P and UL3-500P) with sensibility regulation (2m to 12m) and activation time regulation (2s to 120s)

Lumens	500 lm
Lumens in permanent mode	1710 lm
Color temperatures (K)	4000
Light source	Led
Autonomy (h)	3h
Battery	2 x Ni-MH 3,6V/2700mAh
Power (W)	0W
Operating mode	Maintained - Non Maintained
Class	II
IP	65
IK	10
Operating temperature (°C)	5 to 35

**Photometric data:**

**Dimensions (mm):**

