


Ref. D3-200L



Technical drawing of the front view of a rectangular metal plate. The overall width is 322,8 mm and the overall height is 120,5 mm. The plate features rounded corners with a radius of R14 mm. There are four mounting holes, each with a diameter of $\varnothing 14$ mm, located at the corners. The distance between the centers of the mounting holes is 274 mm horizontally and 145 mm vertically. The distance from the center of a mounting hole to the nearest edge is 109 mm horizontally and 62 mm vertically. The plate has a thickness of 18,34 mm. The bottom edge of the plate is shown with a 45-degree chamfer.



UNE 60598-2-22
230V 50HZ

Alumbrado de Emergencia: DUNNA. Referencia: D3-200L, fabricado por Normalux. Lúmenes 200 lm. Autonomía (h) 3h. Modo de funcionamiento: No permanente. Tipo de instalación: Superficie. Fuente de Luz: Led. Batería de: Ni-Cd 7,2V/750mAh. IP: 44. IK: 07. Versión: Estándar. Acabado: Blanco. Carcasa de: PC+ABS Autoextinguible. Voltaje: 230V 50Hz. Dimensiones (mm): 322 x 125 x 45 mm. Manufacturado según la normativa UNE 60598-2-22. Compatible con telemando S-TE.

Lúmenes	200 lm
Temperatura de color (K)	5700
Fuente de Luz	Led
Autonomía (h)	3h
Batería	Ni-Cd 7,2V/750mAh
Tiempo de carga	max. 24 h
Potencia (W)	1,2W
Modo de funcionamiento	No permanente
Clase	II
IP	44
IK	07
Temperatura de funcionamiento (°C)	5 a 35
Telemandable	Si