

AENOR

ENEC Certification Body registered under ID # 01. For further information, please consult www.enec.com

LICENCE

to use the European Mark



Licence Nr. ENEC/001288

Under the conditions given in the following pages of this document, the licence to use the ENEC Mark in conjunction with the suffix 01, as shown above, has been issued to:

NORMAGRUP TECHNOLOGY, S.A.
Parque TECNOLÓGICO ASTURIAS
33428 LLANERA (Asturias – España / Spain)

For the product(s):

LED luminaires for emergency lighting

Trade name(s):

NORMALUX

Complying with the following European Standards:

EN IEC 60598-1:2021; EN IEC 60598-1:2021/A11:2022;
EN IEC 60598-2-22:2022;
EN 62262:2002; EN 62262:2002/A1:2021

Date: 2025-03-19

Signature:

A handwritten signature in blue ink, appearing to read 'Rafael García', with a stylized flourish at the end.

Name: Rafael García

Position: Chief Executive Officer

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

AENOR CONFÍA, S.A.U.
Cl Génova, 6
28004 MADRID (Spain)

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type of Product	LED LUMINAIRES FOR EMERGENCY LIGHTING
r1) Certificate n°	ENEC/001288
r2) Date of the Certificate	2025-03-19
r3) report n°	2023040236B1-A1
r4) Name and address of the licensee	NORMAGRUP TECHNOLOGY, S.A. Parque TECNOLÓGICO ASTURIAS 33428 LLANERA (Asturias - España / Spain)
r5) Address of the factory	PQ TECNOLÓGICO ASTURIAS - PARCELA, 10 33428 LLANERA (Asturias - España / Spain)
r6) European Standard	EN IEC 60598-1:2021; EN IEC 60598-1:2021/A11:2022; EN IEC 60598-2-22:2022; EN 62262:2002; EN 62262:2002/A1:2021
r7) Type reference	See above for details
r8) Trade Mark	NORMALUX
r9) Rated voltage and frequency	230 V~; 50/60 Hz
r10) N° lamps x rated power, type and lampholder	1 x 0,5 W; LED module
r11) IP degree of protection	See above for details
r12) Power supply connection means	Terminals
r13) Classif. per holding surface material	Suitable for normally flammable surfaces
r14) Protection against electric shocks (class)	Class II
r15) Rated lumen output and duration	See above for details
r16) Battery features	See above for details
r17) Additional information	See above for details
r18) General data	Protections: by PTC
Date of expiry: 2030-03-07	This certificate supersedes certificate 007/001288, dated 2025-03-07.

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	IP degree of protection	Rated lumen output and duration	Battery features	Additional information
QAL-150Li	IP 44, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Autotest. Maintained
QAL-250Li	IP 44, IK 09	230 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Autotest. Maintained
QAL3-250Li	IP 44, IK 09	235 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Autotest. Maintained
QA-300L	IP 44, IK 09	265 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Autotest. Non-maintained
QEAL-150Li	IP 65, IK 09	125 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QEAL-250Li	IP 65, IK 09	225 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QEAL3-250Li	IP 65, IK 09	235 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QEA-300L	IP 65, IK 09	265 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Outdoor. Autotest. Non-maintained
QEIDL-150Li	IP 65, IK 09	125 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Intelligent. Maintained
QEIDL-250Li	IP 65, IK 09	225 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Intelligent. Maintained
QEIDL3-250Li	IP 65, IK 09	235 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Intelligent. Maintained
QIDL-150Li	IP 44, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Intelligent. Maintained. Remote rest
QIDL-250Li	IP 44, IK 09	230 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Intelligent. Maintained. Remote rest
QIDL3-250Li	IP 44, IK 09	235 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Intelligent. Maintained. Remote rest
QSAL-150Li	IP 44, IK 09	135 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Autotest. Maintained
QSAL-250Li	IP 44, IK 09	235 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Autotest. Maintained
QSAL3-250Li	IP 44, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Autotest. Maintained
QSA-300L	IP 44, IK 09	280 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Autotest. Non-maintained
QSEAL-150Li	IP 65, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QSEAL-250Li	IP 65, IK 09	235 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	IP degree of protection	Rated lumen output and duration	Battery features	Additional information
QSEAL3-250Li	IP 65, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QSEA-300L	IP 65, IK 09	300 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Outdoor. Autotest. Non-maintained
QSEIDL-150Li	IP 65, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Intelligent. Maintained
QSEIDL-250Li	IP 65, IK 09	235 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Intelligent. Maintained
QSEIDL3-250Li	IP 65, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Intelligent. Maintained
QSIDL-150Li	IP 44, IK 09	135 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Intelligent. Maintained. Remote rest
QSIDL-250Li	IP 44, IK 09	250 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Intelligent. Maintained. Remote rest
QSIDL3-250Li	IP 44, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Intelligent. Maintained. Remote rest
QVAL-150Li	IP 44, IK 09	135 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Autotest. Maintained
QVAL-250Li	IP 44, IK 09	250 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Autotest. Maintained
QVAL3-250Li	IP 44, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Autotest. Maintained
QVA-300L	IP 44, IK 09	280 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Autotest. Non-maintained
QVEAL-150Li	IP 65, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QVEAL-250Li	IP 65, IK 09	235 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QVEAL3-250Li	IP 65, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Autotest. Maintained. Remote rest
QVEA-300L	IP 65, IK 09	280 lm - emergency; 1 h	NiMH 3,6 V 1200 mAh	Series Arque. Outdoor. Autotest. Non-maintained
QVEIDL-150Li	IP 65, IK 09	130 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Outdoor. Intelligent. Maintained
QVEIDL-250Li	IP 65, IK 09	235 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Outdoor. Intelligent. Maintained
QVEIDL3-250Li	IP 65, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Outdoor. Intelligent. Maintained
QVIDL-150Li	IP 44, IK 09	135 lm - emergency; 1 h	LiFePO4 3,2 V 600 mAh	Series Arque. Intelligent. Maintained. Remote rest

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	IP degree of protection	Rated lumen output and duration	Battery features	Additional information
QVIDL-250Li	IP 44, IK 09	250 lm - emergency; 1 h	LiFePO4 3,2 V 1500 mAh	Series Arque. Intelligent. Maintained. Remote rest
QVIDL3-250Li	IP 44, IK 09	250 lm - emergency; 3 h	LiFePO4 3,2 V 3000 mAh	Series Arque. Intelligent. Maintained. Remote rest