




New




Hermetic EX



Maintained led



Non-maintained multiled



Version of the emergency luminaire HERMETIC that can be used in Category 3 locations according ATEX 2014/34/UE.



EN 60598-2-22



Can be used in locations designated Category 3 in accordance with Directive ATEX 2014/34/UE.


Zones 2, 22

Hermetic EX

Standard

Non-maintained MULTILED

IP 65

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
DE-60LEX	White	—	40 lm	1 h	0,7	20
DE-100LEX	White	—	55 lm	1 h	0,7	20
DE-150LEX	White	—	65 lm	1 h	0,7	20
DE-200LEX	White	—	105 lm	1 h	0,7	20
DE-300LEX	White	—	165 lm	1 h	0,7	20
DE-400LEX	White	—	230 lm	1 h	0,8	20
DE-500LEX	White	—	290 lm	1 h	0,8	20
DE3-60LEX	White	—	60 lm	3 h	0,7	20
DE3-200LEX	White	—	105 lm	3 h	0,8	20

Available in 127v AC 50/60Hz. Indicate reference + V.
Available in 24v DC. Indicate reference + C.

Maintained MULTILED

IP 65

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
DEL-60EX	White	—	40 lm	1 h	0,7	20
DEL-150EX	White	—	100 lm	1 h	0,7	20
DEL-200EX	White	—	170 lm	1 h	0,7	20
DEL-300EX	White	—	185 lm	1 h	0,7	20
DEL2-200EX	White	—	150 lm	2 h	0,7	20
DEL3-100EX	White	—	70 lm	3 h	0,7	20


Available in 127v AC 50/60Hz. Indicate reference + V.
Available in 24v DC. Indicate reference + C.

Accessories

Blade diffuser



DE-DB Blade diffuser with PVC screws for the HERMETIC EX range




Remote controls





S-TE Remote control for up to 300 fittings standard or autotest

Pictograms

Type LN Adhesive pictogram 230 x 110 mm. *References according to table below*

 Please check for other pictograms

Type LN 230 x 110 mm

REF. LN-L	REF. LN-R	REF. LN-SD	REF. LN-SU
			

Maximum viewing distance
(according to EN1838 for internally illuminated signs)

22 m