





Now
with LiFePO4
lithium batteries

Excellence



! Quick assembly

The EXCELLENCE emergency fittings are our bet on design and functionality. They are luminaires that are fully made from polycarbonate with stylish shapes that make them ideal for mounting on the wall/ ceiling or recessed mounting.



Lm
110-330

1-2-3



Ni-Cd
LiFePO4

IP
42

IK
04

230 Vac
24 Vdc



EN 60598-2-22


+ Remote controlled

Excellence

Standard

Non-maintained MULTILED

IP
42


	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
E-200L	White	—	200 lm	1 h	1,1	12
E-300L	White	—	300 lm	1 h	1,1	12

Autotest




Non-maintained MULTILED

IP
42

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EA-200L	White	—	180 lm	1 h	1,1	12
EA-300L	White	—	300 lm	1 h	1,2	12

Maintained / Non-maintained MULTILED

IP
42


	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EAL-200M	White	—	180 lm	1 h	1,1	12
EAL-250M	White	—	250 lm	1 h	1,1	12
LITHIUM EAL-250LI	White	—	240 lm	1 h	1,1	12
EAL-300M	White	—	330 lm	1 h	1,2	12
EAL3-100M	White	—	110 lm	3 h	1,1	12
LITHIUM EAL3-250LI	White	—	240 lm	3 h	1,2	12

Intelligent DALI

Compatible with **NormaLINK** 

Maintained / Non-maintained MULTILED

IP
42

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
LITHIUM EIDL-250M	White	DALI	250 lm	1 h	1,1	12
EIDL-250LI	White	DALI	240 lm	1 h	1,2	12
EIDL-300M	White	DALI	330 lm	1 h	1,2	12
EIDL3-100M	White	DALI	110 lm	3 h	1,1	12
LITHIUM EIDL3-250LI	White	DALI	240 lm	3 h	1,2	12

Intelligent Wireless



New

Maintained / Non-maintained MULTILED


IP
42

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EIDL-300M-R	White	DALI	330 lm	1 h	1,2	12
EIDL3-100M-R	White	DALI	110 lm	3 h	1,1	12

Central Battery System

Maintained MULTILED

IP
42

	FINISHING	POWER SUPPLY	LUMEN OUTPUT	CONSUMPTION	CURRENT		PACKAGING
C24 E-S24L24	White	24 Vcc	306 lm	2,64 W	0,11 A	1,0	12
C24i EI-S25L24	White	24 Vcc	240 lm	3 W	0,125 A	1,1	12
E-S24L	White	230 Vca	320 lm	3,7 W	0,019 A	1,2	12

Excellence Accessories

**FALSE CEILING RECESSED
MOUNTING** (accessory included)



SURFACE MOUNTING
(accessory included)



Tube cable entry

O-AT M20 tube mounting accessory.
Adapter included free of charge.

Minitrunking
cable entry

The fitting has three entries for minitrunking, 20 x 10mm

Recession frames

This fitting does not require any recession frame.
Two metal clips are supplied with it free of charge

Aluminium frame



E-MD Improves the aesthetics making it more modern.
It is needed for the installation of the non adhesive pictogram.

Light orientator



E-OL Aluminium sheet to be installed over the diffuser and direct the light
to the flag diffuser, avoiding the glare

Excellence Accessories

Wall and ceiling mounting accessories



O-KS 30/100

OKS-30	300 mm metal rod for ceiling suspension
OKS-100	1000 mm metal rod for ceiling suspension
E-SBT	Ceiling accessory
E-SB	Wall accessory



E-SB

Remote controls

S-TE	Remote control for up to 300 fittings standard or autotest
-------------	--

Check other control options on page 158

Serigraphed methacrylate blade diffusers



E-DB	E-DB transparent blade diffuser (includes the clips for installation) PAB type pictogram included
-------------	--

The methacrylate pictograms are offered with the wall fixation bracket. The transparent blade diffuser (Ref: E-DB) can also be used with any of the adhesives for any other use

Type PAB 350 x 150 mm		Maximum viewing distance (according to EN1838 for internally illuminated signs) 30 m
REF. PAB-A	REF. PAB-A	REF. PAB-SD
		REF. PAB-SU

Pictograms

Type PAM	Non adhesive pictogram 350x168 mm. To be used on the E-MD accessorie (not included)
Type PE	Adhesive pictogram 355 x 150 mm to be placed on the cover of the emergency light

Type PAM 350 x 168 mm		Maximum viewing distance (according to EN1838 for internally illuminated signs) 36 m
REF. PAM-L	REF. PAM-R	REF. PAM-SD
		REF. PAM-SU

Type PE 355 x 150 mm	
REF. PE-L	REF. PE-R
	REF. PE-SD
	REF. PE-SU

Please check for other pictograms