




# Watertight self-contained fittings



	A	B	C	D
1x18	680	105	120	500
2x18	680	175	120	500
1x36	1.280	105	120	912
2x36	1.280	175	120	912
1x58	1.600	105	120	995
2x58	1.600	175	120	995

□ CE 850°C



Lm  
280-1872



Ni-Cd

IP  
65



230 Vac

EN 60598-2-22  
EN 20392-93



Remote controlled

# Watertight self-contained fittings

IP  
65

	DESCRIPTION	LUMEN OUTPUT	AUTONOMY
<b>MES2FL36C</b>	2 x 36 fitting – 1 maintained + 1 emergency	837 lm	1 h
<b>MESFL36</b>	1 x 36 fitting – emergency	837 lm	1 h
<b>MES2FL36P</b>	2 x 36 fitting – 2 maintained + 1 emergency	837 lm	1 h
<b>MESFL36P</b>	1 x 36 fitting – maintained + emergency	837 lm	1 h
<b>MES2FL58C</b>	2 x 58 fitting – 1 maintained + 1 emergency	936 lm	1 h
<b>MESFL58</b>	1 x 58 fitting – emergency	936 lm	1 h
<b>MES2FL58P</b>	2 x 58 fitting – 2 maintained + 1 emergency	936 lm	1 h
<b>MESFL58P</b>	1 x 58 fitting – maintained + emergency	936 lm	1 h
<b>MES2FL36</b>	2 x 36 fitting – 2 emergency	1674 lm	1 h
<b>MES2FL36P2E</b>	2 x 36 fitting – 2 maintained + 2 emergency	1674 lm	1 h
<b>MES2FL58</b>	2 x 58 fitting – 2 emergency	1872 lm	1 h
<b>MES2FL58P2E</b>	2 x 58 fitting – 2 maintained + 2 emergency	1872 lm	1 h
<b>MES2FL18C</b>	2 x 18 fitting – 1 maintained + 1 emergency	526 lm	2 h
<b>MESFL18</b>	1 x 18 fitting – emergency	526 lm	2 h
<b>MESFL18P</b>	1 x 18 fitting – maintained + emergency	526 lm	2 h
<b>MES2FL18</b>	2 x 18 fitting – 2 emergency	1052 lm	2 h
<b>MES2FL18P</b>	2 x 18 fitting – 2 maintained + 1 emergency	1052 lm	2 h
<b>MES2FL18P2E</b>	2 x 18 fitting – 2 maintained + 2 emergency	280 lm	2 h

## Accessories

### Remote controls

**S-TE** Remote control for up to 300 fittings standard or autotest

