




Explosion proof




CATEGORY 2
ACCORDING TO
ATEX 2014/34/UE



— C0-C180 Cd/klm
— C90-C270 $\eta=100\%$

The EXPLOSION PROOF range has been specifically designed to be used in explosive atmospheres that have been designated category II in accordance with Directive ATEX 2014/34/UE.



Lm
200-400

1



IP
67

IK
06



EN 60598-2-22
EN50018



Wall mounting plate
not included.
Anti explosion cable
glands not included.



Remote controlled.

Valid for sites designated category II in accordance with Directive ATEX 2014/34/UE.

Zone: 1, 21. Exd. IIC T6.

Explosion proof

Standard

Non-maintained / Fluorescent

IP
67

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EX-200	Glass	—	200 lm	1 h	5,1	1
EX-400	Glass	—	400 lm	1 h	5,5	1

Autotest

Non-maintained / Fluorescent

IP
67

	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EXA-200	Glass	—	200 lm	1 h	5,3	1
EXA-400	Glass	—	400 lm	1 h	5,4	1

Intelligent DALI

Compatible with **NormaLINK** 



Non-maintained / Fluorescent

IP
67


	FINISHING	COM.	LUMEN OUTPUT	AUTONOMY		PACKAGING
EXID-200	Glass	DALI	200 lm	1 h	5,0	1
EXID-400	Glass	DALI	400 lm	1 h	5,4	1

Accessories

Remote controls



S-TE Remote control for up to 300 fittings standard or autotest



Wall mounting

BRIDAEX Wall mounting accessory

Exit signs

