

Step lighting




Step light for
universal box

24V CBS
version available



Estela recessed mounted



REF: **ET**

REF: **ER**

REF: **EC**

Finishing:

Grey: RAL7047

Anthracite: RAL7015

Aluminium: RAL7004

Technical features::

- Universal box installation.
- Reference regulations EN 60598-1
- Power 230V, 50/60 Hz.
- Versions for 127V 50/60Hz and 24V DC.
- Housing and diffuser: Polycarbonate
- Class II. IP-44. IK-07
- Can be mounted on a flammable surface.
- Charging time 24 hours.
- Possibility of remote control.
- Different light colours.

24v DC version is compatible with the C24 central battery system (information on page 158) and with the power supply module for step lights MA24-6 (information on page 140).

Estela recessed mounted

IP
44

	FINISHING	LAMP	COLOUR LED	AUTONOMY	BATTERY	COS (φ)	CONSUMPTION	PACKAGING
EC-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
EC-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
EC-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20

Available 24v DC, ref: + Y

Accessories

Remote controls

S-TE

Remote control for up to 300 fittings standard or autotest

Step lighting

CE 850°C LED




Surface mounted step light

24V CBS version available



Estela surface mounted



REF: ET

REF: ER

REF: EC

Finishing:

Grey: RAL7047

Anthracite: RAL7015

Aluminium: RAL7004

Technical features:

- Surface mounted.
- Reference regulations EN 60598-1
- Power 230V, 50/60 Hz.
- Versions for 127V 50/60Hz and 24V DC.
- Housing and diffuser: Polycarbonate
- Class II. IP-44. IK-07
- Can be mounted on a flammable surface.
- Charging time 24 hours.
- Possibility of remote control.
- Different light colours.

24v DC version is compatible with the C24 central battery system (information on page 158) and with the power supply module for step lights MA24-6 (information on page 140).

Estela surface mounted

IP
44

	FINISHING	LAMP	COLOUR LED	AUTONOMY	BATTERY	COS (φ)	CONSUMPTION	PACKAGING
EC-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
EC-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
EC-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ER-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ET-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ECV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ERV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
ETV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20

Available 24v DC, ref: + Y

Accessories

Remote controls

S-TE

Remote control for up to 300 fittings standard or autotest