

Step lighting




Step light for universal box

24V CBS
version available



Senda recessed mounted



REF: NT

REF: NR

REF: NC

Finishing:

Grey: RAL7047
Anthracite: RAL7015
Aluminium: RAL7004

Technical features:

- Universal box installation.
- Reference norms EN 60598-1
- Power 230V, 50/60 Hz.
- Versions for 127V 50/60Hz and 24V DC.
- Housing and diffuser: Polycarbonate
- Class II. IP-44. IK-07
- Can be mounted on a flammable surface.
- Charging time 24 hours.
- Possibility of remote control.
- Different light colours.

24v DC version is compatible with the C24 central battery system (information on page 158) and with the power supply module for step lights MA24-6 (information on page 140).

Senda recessed mounted

IP
44

	FINISHING	LAMP	COLOUR LED	AUTONOMY	BATTERY	COS (φ)	CONSUMPTION	PACKAGING
NC-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NC-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NC-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-E	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-E-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-E-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-E	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-E-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-E-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-E	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-E-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-E-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-E	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-E-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-E-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20

Available 24v DC, ref: + Y

Accessories

Remote controls

S-TE

Remote control for up to 300 fittings standard or autotest

Step lighting

CE 850°C LED




Surface mounted step light

24V CBS
version available



Senda surface mounted



REF: NT

REF: NR

REF: NC

Finishing:

Grey: RAL7047

Anthracite: RAL7015

Aluminium: RAL7004

Technical features:

- Surface mounted.
- Reference regulations EN 60598-1
- Power 230V, 50/60 Hz.
- Versions for 127V 50/60Hz and 24V DC.
- Housing and diffuser: Polycarbonate.
- Class II. IP-44. IK-07
- Can be mounted on a flammable surface.
- Charging time 24 hours.
- Possibility of remote control.
- Different light colours.

24v DC version is compatible with the C24 central battery system (information on page 158) and with the power supply module for step lights MA24-6 (information on page 140).

Senda surface mounted

IP
44

	FINISHING	LAMP	COLOUR LED	AUTONOMY	BATTERY	COS (φ)	CONSUMPTION	PACKAGING
NC-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NC-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NC-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NR-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-S	Grey	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-S-1	Anthracite	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NT-S-2	Aluminium	LED	White	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-S	Grey	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-S-1	Anthracite	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTA-S-2	Aluminium	LED	Blue	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-S	Grey	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-S-1	Anthracite	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTR-S-2	Aluminium	LED	Red	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NCV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NRV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-S	Grey	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-S-1	Anthracite	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20
NTV-S-2	Aluminium	LED	Green	1 h	3,6 V · 60 mAh	0,07	0,35 W	20

Available **24v DC**, ref: + Y

Accessories

Remote controls

S-TE

Remote control for up to 300 fittings standard or autotest