




Kenlux

Características técnicas:

- Kit para la conversión en alumbrado autónomo.
- Norma de referencia: EN 60924.
- Señalización de carga mediante LED.
- Alimentación 230V, 50/60 Hz.
- Tiempo de recarga: 24 horas.
- Telemandable.



	A	B	C	D	E	F
KEN 1-18	163	32	173	39	127	22
KEN 3-18	163	32	173	39	176	33
KEN 1-36	163	32	173	39	127	22
KEN 3-36	163	32	173	39	176	33
KEN 1-58	163	32	173	39	169	22
KEN 3-58	163	32	173	39	235	33
KEN S1UNIV	163	32	173	39	295	33
KEN 1-14 T5	163	32	173	39	353	33
KEN 1-21 T5	163	32	173	39	353	33
KEN 1-24 T5	163	32	173	39	353	33
KEN 1-28 T5	163	32	173	39	353	33
KEN 1-35 T5	163	32	173	39	353	33
KEN 1-39 T5	163	32	173	39	353	33
KEN 1-49 T5	163	32	173	39	353	33
KEN 1-54 T5	163	32	173	39	353	33
KEN1-UNI	41	239	44	295	33	

Kenlux

Estándar

	BATERÍA	AUTONOMÍA	RENDIMIENTO	EMBALAJE
KEN1-18	3,6 V · 1,5 Ah	18W: 1 hora	18W: 17%	20
KEN3-18	3,6 V · 4,0 Ah	18W: 3 horas	18W: 12%	20
KEN1-36	3,6 V · 1,5 Ah	36W: 1 hora	18W: 17% - 36W: 8%	20
KEN3-36	3,6 V · 4,0 Ah	36W: 3 horas	18W: 17% - 36W: 8%	20
KEN1-58	4,8 V · 1,5 Ah	58W: 1 hora	58W: 8%	20
KEN3-58	4,8 V · 4,0 Ah	58W: 3 horas	58W: 6,5%	20
KENS1-UNI	6,0 V · 4,0 Ah	18W: 2 horas 36W: 1,5 horas 58W: 1 hora	18W: 39% 36W: 25% 58W: 18%	20
KEN1-14T5	7,2 V · 4,0 Ah	14W TL5 HE: 1 hora	14W TL5 HE: 63%	20
KEN1-21T5	7,2 V · 4,0 Ah	21W TL5 HE: 1 hora	21W TL5 HE: 51%	20
KEN1-24T5	7,2 V · 4,0 Ah	24W TL5 HO: 1 hora	24W TL5 HO: 44%	20
KEN1-28T5	7,2 V · 4,0 Ah	28W TL5 HE: 1 hora	28W TL5 HE: 42%	20
KEN1-35T5	7,2 V · 4,0 Ah	35W TL5 HE: 1 hora	35W TL5 HE: 31%	20
KEN1-39T5	7,2 V · 4,0 Ah	39W TL5 HO: 1 hora	39W TL5 HO: 26%	20
KEN1-49T5	7,2 V · 4,0 Ah	49W TL5 HO: 1 hora	49W TL5 HO: 24%	20
KEN1-54T5	7,2 V · 4,0 Ah	54W TL5 HO: 1 hora	54W TL5 HO: 21%	20










Inteligente DALI

Compatible con **NormaLINK** 



	BATERÍA	AUTONOMÍA	RENDIMIENTO	EMBALAJE
KEN1-UNI	6,0V 4,0Ah	18W: 2 horas 36W: 1,5 horas 58W: 1 hora	18W: 39% 36W: 25% 58W: 18%	20

KENS1-UNI. Compatibilidad y autonomía

	LÁMPARA	PLAMP (W/h)	LÚMENES TEÓRICOS	BLF	FLUJO LUMINOSO (lm)
	TC-DEL 18W	18	1200	43%	510
	TC-DEL 26W	26	1800	34%	604
	TC-TEL 18W	18	1200	37%	445
	TC-TEL 32W	32	2400	24%	584
	TC-TEL 42W	42	3200	23%	733
	T8-18W	18	1350	39%	528
	T8-36W	36	3350	24%	806
	T8-58W	58	5200	18%	951
	T5-HE 14W	14	1350	41%	548
	T5-HE 21W	21	2100	39%	822
	T5-HO 24W	24	2000	32%	643
	T5-HO 39W	39	3500	26%	902
	TC-L 18W	18	1200	31%	367
	TC-L 24W	24	1800	34%	604
	TC-L 36W	36	2900	28%	810
	TC-L 55W	55	4800	19%	894
	TC-F 18W	18	1100	21%	230
	TC-F 24W	24	1700	19%	328
	TC-F 36W	36	2800	21%	596
	TC-DD 21W	21	1500	37%	550
	TC-DD 28W	28	2050	32%	665
	FC-22W	22	875	38%	332
	FC-32W	32	1550	34%	528
	FC-40W	40	2090	34%	709

*BLF: Porcentaje potencia lumínica emitida / potencia lumínica nominal de la lámpara.