




# Versatile



## Technical features:

- 230V 50/60 Hz.
- Norms EN 55015, EN 61347-2-7, EN 61000-3-2.
- Low Power Directive EC 72/23/CE.
- Electromagnetic Compatibility Directive 2004/108/CE.
- Temperature: 10°C a 40°C.
- Batteries: two options available changing the position of an internal bridge:
  - Batteries Ni/Cd de 7.2V/1.5Ah 1 h Autonomy.
  - Batteries Ni/Cd de 7.2V/4 Ah 3 h Autonomy.
- Physical features:
  - Size: 316 mm x 32mm x 25 mm (height)
  - Housing: Polycarbonate plastic.
  - Cage clamps in the input and output for lamps and connection to electronic ballast.
- Others:
  - Green Led to show the correct charge of the batteries.
  - Compatible with all the electronic ballasts.
  - Compatible with Normalux' remote control S-TE.
- Lamps:
  - Can be used with all fluorescent lamps from 18W to 58W










	A	B	C	D	E	F
VKIT	316	25	32	304	255	23
VKIT3	316	25	32	304	360	33

# Versatile

IP 20

	BATTERY	AUTONOMY	PACKAGING
<b>VKIT</b>	7,2 V · 1,5 Ah	1 h	20
<b>VKIT3</b>	7,2 V · 4,0 Ah	3 h	20

## VERSATILE. Compatibility and duration

	LAMP	PLAMP (W/h)	THEORETICAL LUMEN OUTPUT	BLF	LUMEN OUTPUT (lm)
	<b>TC-DEL 18W</b>	18	1200	18%	220
	<b>TC-DEL 26W</b>	26	1800	16%	286
	<b>TC-TEL 18W</b>	18	1200	16%	191
	<b>TC-TEL 32W</b>	32	2400	9%	219
	<b>TC-TEL 42W</b>	42	3200	10%	320
	<b>T8-18W</b>	18	1350	14%	195
	<b>T8-36W</b>	36	3350	10%	342
	<b>T8-58W</b>	58	5200	7%	366
	<b>T5-HE 14W</b>	14	1350	20%	274
	<b>T5-HE 21W</b>	21	2100	14%	300
	<b>T5-HE 28W</b>	28	2900	14%	415
	<b>T5-HO 24W</b>	24	2000	14%	274
	<b>T5-HO 39W</b>	39	3500	11%	377
	<b>T5-HO 54W</b>	54	5000	8%	389
	<b>T5-HE 35W</b>	35	3650	12%	437
	<b>TC-L 18W</b>	18	1200	13%	152
	<b>TC-L 24W</b>	24	1800	15%	262
	<b>TC-L 36W</b>	36	2900	11%	320
	<b>TC-L 55W</b>	55	4800	10%	457
	<b>TC-F 18W</b>	18	1100	10%	110
	<b>TC-F 24W</b>	24	1700	11%	195
	<b>TC-F 36W</b>	36	2800	10%	276
	<b>TC-DD 21W</b>	21	1500	15%	218
	<b>TC-DD 28W</b>	28	2050	14%	284
	<b>FC-22W</b>	22	875	17%	147
	<b>FC-32W</b>	32	1150	18%	211
	<b>FC-40W</b>	40	2090	13%	282

\*BLF: Percentage of luminic power emmitted / nominal luminic power of the lamp.

## Accessories

### Remote controls



**S-TE** Remote control for up to 300 fittings standard or autotest

