

Designed for security

Emergency lighting

Gennius


The GENNIUS range of emergency lighting is a superb combination of design and practicality. But what really makes GENNIUS outstanding are the invisible details: IP68, IK10 for a robust system that can withstand any situation.

There are also numerous accessories that make the GENNIUS family an extremely versatile option for even complex installations.



IP
68

IK
10



Easy to install

The R&D team at Normagrup has made this range exceptionally easy to install, with **plug-in terminals** and plenty of space inside for cabling. The pictogram can be easily placed.

Up to four M20 inputs

Two are cut out for easy mounting, which are concealed in a semi-recessed installation.

More compatible

Compatible mounting with other installations makes it easy to replace other emergency luminaires.

NORMALUX

Emergency lighting
normalux.com



Gennius


Emergency lighting




Technical features

- Housing made from self-extinguishing ABS.
- Polystyrene diffuser.
- Installation: ceiling or wall mounted (can also be semi-recessed using a recession frame).
- Light range: 95-300 lm.
- Autonomy options: 1-3 h.
- Light source: LED.
- Batteries: Ni-Cd (high temperature) and Li (Lithium), Ni-MH
- Modes of operation:
 - Non-maintained.
 - Maintained / Non maintained.
- Versions: Standard, Autotest, Intelligent DALI and Central Battery System.
- IP 68. IK 10.
- Can be mounted on flammable surfaces.
- Charging LED.
- Test button.
- Possibility of remote control.
- Power: 230 V · 50/60 Hz.
- Charging time 24 hours.
- Manufactured according to EN 60598-2-22.

Quick installation system



1 M20 cable gland (not included)



Easy to place

Gennius + pictogram PG-L

STANDARD

Non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GE-100L	-	95 lm	1 h	0,3 20
GE-200L	-	200 lm	1 h	0,3 20
GE-300L	-	300 lm	1 h	0,3 20
GE3-100L	-	100 lm	3 h	0,3 20

Maintained / non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GEL-100	-	95 lm	1 h	0,3 20
GEL-200	-	195 lm	1 h	0,3 20
GEL-300	-	300 lm	1 h	0,3 20
GEL-400	-	400 lm	1 h	0,3 20
GEL3-100	-	90 lm	3 h	0,3 20

AUTOTEST

Non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GEA-100L	-	100 lm	1 h	0,3 20
GEA-200L	-	200 lm	1 h	0,3 20
GEA-300L	-	300 lm	1 h	0,3 20
GEA3-100L	-	100 lm	3 h	0,3 20

Maintained / non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GEAL-100	-	100 lm	1 h	0,3 20
GEAL-200	-	200 lm	1 h	0,3 20
LITHIUM GEAL-250LI	-	250 lm	1 h	0,3 20
GEAL-300	-	300 lm	1 h	0,3 20
GEAL-400	-	400 lm	1 h	0,3 20
LITHIUM GEAL-500LI	-	500 lm	1 h	0,3 20
GEAL3-100	-	100 lm	3 h	0,3 20

INTELLIGENT DALI



Compatible with **NormaLINK**

Non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GEID-100L	DALI	100 lm	1 h	0,4 20
GEID-200L	DALI	200 lm	1 h	0,4 20
GEID-300L	DALI	300 lm	1 h	0,4 20
GEID3-100L	DALI	100 lm	3 h	0,4 20

Maintained / non-maintained MULTILED



	COM.	LUMEN OUTPUT	AUTONOMY	PACKAGING
GEIDL-100	DALI	100 lm	1 h	0,6 20
GEIDL-200	DALI	200 lm	1 h	0,6 20
LITHIUM GEIDL-250LI	DALI	250 lm	1 h	0,6 20
GEIDL-300	DALI	300 lm	1 h	0,6 20
GEIDL-400	DALI	400 lm	1 h	0,6 20
LITHIUM GEIDL-500LI	DALI	500 lm	1 h	0,6 20
GEIDL3-100	DALI	100 lm	3 h	0,6 20

CENTRAL BATTERY SYSTEM

	POWER SUPPLY	LUMEN OUTPUT	CONSUMPTION	CURRENT	PACKAGING	
C24	GE-S24L24	24 Vcc	300 lm	3 W	0,14 A	0,6
C24i	GEI-S24L24	24 Vcc	300 lm	4 W	0,18 A	0,6

ACCESSORIES

Flag light deflector	GE-DB	GE-DB Flag light deflector for devices compatible with the Gennius range
Installation accessory	GE-MSE	Installation accessory for semi-recessed installation
Surface installation	GE-PP	Pre-assembly plate for surface mounting
Fixation	GE-SBT	Wall accessory
Remote control	S-TE	Remote control for up to 300 fittings
Pictograms	Type PG	Type PG Non-adhesive pictograms 300x150 mm:

Maximum viewing distance (according to EN 1838 for internally)

30 m



Type PGB Type PGB Non-adhesive pictograms 300x150 mm for GE-DB accessory:



Headquarters

Parque Tecnológico de Asturias. C/ Ablanal, 1
33428 Llanera (Asturias)
España / Spain
normagrup.com